J355 F M30-P1

Fixed security bollard

Type of operator

Fixed

Height

1,000 mm

- Tested according to the American standard ASTM F 2656.
- «Shallow Mounted» product: very low excavation depth needed.
- Total aesthetic consistency with other retractable bollards (HA); perfect for mixed installations.

CE

DIMENSIONS AND TECHNICAL SPECIFICATIONS

Model	J355 F M30-P1	J355 F M30-P1 INOX
Cylinder height from ground	1,000 mm	
Cylinder diameter	355 mm	
Cylinder material	S355JR EN 10210 steel	
Cylinder treatment	Cataphoresis and polyester powder paint, dark grey metallised RAL 7021	INOX AISI 316L satin finish
Reflective strip height	55 mm	
Standard reflecting strip colour	White	
Break in resistance	656.000 J	
Total weight	707 Kg	710 Kg
Excavation dimensions (LxWxH)	4.000 x 2.300 x 350mm	4.000 x 2.300 x 350 mm

PAINTED STEEL FAMILY MODELS

Model	Item code
J355 F M30-P1	116321

PACKS

J355 M30-P1 F is equipped with:

- steel cylinder with cataphoresis treatment and metallised dark grey powder coated painting
- flashing LED lights ring*
- underground modular structure

INOX AISI 316L FAMILY MODELS

Model	Item code
J355 F M30-P1	116342

PACKS

J355 M30-P1 F INOX is equipped with:

- steel cylinder with a cataphoretic treatment and a satin-finished stainless steel “sleeve”
- flashing LED lights ring*
- underground modular structure

OPTIONAL ACCESSORIES

J355 M30 ground crown

63000948

NOTE

(*) The power supply unit (24 V) and the cable (2x1.5 mm) for the flashing light are not supplied.