

Road blockers

To secure passages up to 6 m wide



HIGH SECURITY

Road Blocker 500

- For high use frequencies (approx. 2000 cycles / day)
- **Barrier height 500 mm**
- Flush-fitting to floor
- External hydraulic operator (max. distance 30 m)
- Optionally with EFO emergency function (Emergency Fast Operation)



Road Blocker 1000

- For high use frequencies (approx. 2000 cycles / day)
- **Barrier height 1000 mm**
- Flush-fitting to floor
- External hydraulic operator (max. distance 30 m)
- Optionally with EFO emergency function (Emergency Fast Operation)

● Standard equipment ○ Optional equipment

For information about the equipment options, see page 32.

	Road Blocker 500	Road Blocker 1000
Ramp height above ground level	500 mm	300 mm
Standard length	2, 3, 4, 5, 6 m	2, 3, 4, 5, 6 m
Fitting depth	500 mm	300 mm
External hydraulic operator	●	●
Speed, lifting	10 cm/s	14.5 cm/s
Speed, lowering	10 cm/s	14.5 cm/s
EFO emergency function	○	○
Manual operation	○	○
LED lighting strips	○	○
Protective sections	●	●
Load class acc. to EN 124	D400 (40 tonnes)	D400 (40 tonnes)
Cycles (approx. per day)	2000	2000
Overall cycles (max. service life)	3000000	3000000
Certified to		PAS68
Compliant with	M30, K4, PAS68, IWA14-1	M50, K12, IWA14-1
Impact energy with destruction	750000 J	2000000 J