

J200 F

Fixed access control bollard



Type of operator

Fixed

Height

600 mm



- Power supply and wiring not requested
- Simple laying and limited excavation
- Guarantees aesthetic coherency in multiple installations together with retractable bollards.



DIMENSIONS AND TECHNICAL SPECIFICATIONS

Model	J200 F H600	J200 F H600 Stainless steel
Cylinder height from ground	600 mm	
Cylinder diameter	200 mm	
Cylinder material	S235JRG2 EN 10277 steel	AISI 316L satin finish
Cylinder treatment	Cataphoresis and polyester powder paint, dark grey metallised RAL 7021	Satin finish
Reflective strip height	25 mm	
Standard reflecting strip colour	Orange	
Total weight	35 Kg	
Walled in pit with cylinder profile (LxWxH)	400 x 500 x 200 mm	
Excavation dimensions (LxWxH)	700 x 700 x 200 mm	

PAINTED STEEL FAMILY MODELS

Model	Item code
J200 F H600	116506

PACKS

- J200 F is equipped with:**
- steel cylinder with cataphoresis treatment and metallised dark grey powder coated painting

INOX AISI 316L FAMILY MODELS

Model	Item code
J200 F H600	116507

PACKS

- J200 F INOX is equipped with:**
- AISI 316L satin-finished stainless steel cylinder

OPTIONAL ACCESSORIES



LED lights kit J200 ♦

116504

NOTE

- ♦ The power supply unit (24 V) and the cable (2x1.5 mm) for the flashing light are not supplied.