WINGO 3524 HS

SOLEMYO OPERA BLUEBUS 24V

For hi-speed automation of swing gates with leaves up to 3 m or 200 kg, ideal for residential applications.

24 Vdc electromechanical gear motor, surface mounted, with magnetic encoder.

Quick manoeuvres:

90° opening in about 10* seconds.

Reliable: the magnetic encoder ensures the safeguard of set values over time and precise obstacle detection.

Silent: patented layout of internal parts, fewer moving parts.

Easy to install: after the gear motor has been assembled, all electrical connections are made from above.

Pre-assembled travel stops on opening.

Moonclever control unit MC824H:

- simple programming, by means of a single key;
- automatic memorization of limit switches on opening and closing with self-learning function;
- automatic fault diagnostics;
- programming of pause time;
- pedestrian pass door;
- deceleration on opening and closing;
- obstacle detection with dual technology;
- operation in event of power failure by means of optional rechargeable batteries (PS324);
 provision for connection of latest generation resistive
- sensitive edges.

*Considering standard installation, excluding acceleration and deceleration.

CODE	DESCRIPTION	PACK/PALLET
WG3524HS	IRREVERSIBLE, 24 Vdc, FAST, WITH MAGNETIC ENCODER, MECHANICAL STOP ON OPENING AND CLOSING	20

TECHNICAL SPECIFICATIONS

WG3524HS			
24			
5			
120			
PERFORMANCE DATA			
>> 0.04 <<			
1500			
30			
DIMENSIONAL AND GENERAL DATA			
44			
-20 ÷ +50			
920x98x95 h			
6			

UTILISATION LIMITS



DIMENSIONS



EXCLUSIVE PATENTED LAYOUT OF INTERNAL PARTS

USER-FRIENDLY RELEASE WITH

PERSONALISED NICE KEY